



Hood Distribution

501 South Toole Ave
Tucson, AZ 85701
Phone: 1-520-792-9966
www.hooddistribution.com

DOMESTIC PLYWOOD

www.timberproducts.com

Ash	Walnut
Birch	Red Oak
Cherry	Hickory
Knotty Pine	Mahogany
Maple	White Oak
Alder	VG Doug Fir
Shop Grade	Rustic Grades
Beaded Plywood	

Poplar - Poplar/Aspen - FIR - MDF - CROSSBAND CORES
** 4X8-4X10 ** CARB 2 / NAF / TSCA TITLE VI

MELAMINE

www.americanlaminates.com

White	Black	Almond	Hardrock Maple
Chocolate	Pear	Opti-Grey	Spiced Fruitwood
Candlelight			

*All other colors available special order
4x8 Sheets 1/4" - 3/4" Pine Core

DOMESTIC LUMBER

Basswood	Walnut	Birch
Cherry	Ash	Hickory
Maple Hard	Maple Soft	Red Oak
White Oak	Poplar	Alder

4/4 Thru 8/4 - RW/RL

Surfaced options available

IMPORT LUMBER

Spanish Cedar	African Mahogany
Jatoba	Ipe
Wenge	African Teak
Sapele	Mesquite (Slabs Avail)
Guanacoste	Tigerwood (Goncalo Alves)

KNAPE & VOGT

www.kv.com

Sliding Systems - Barn Door Hardware -
Standards & Brackets - Kitchen & Bath

SALICE HINGES & ACCESSORIES

www.saliceamerica.com

IMPORT PLYWOOD

Birch White	African Mahogany
Meranti/Lauan	alder
Poplar	Red Oak
*Russian Birch	Maple
Falcotta Lumbercore	Bending Poplar
Aromatic Cedar	Bending Meranti

2.7mm-18mm 4x8

5x5 & 4x8 Upersand & Prefinished Options Available

COMPOSITE PLYWOOD

MDF - 1/8" - 1 - 1/8"

Industrial Particleboard - 1/2" - 1"

RATED PLYWOOD

OSB - 7/16" - 23/32"

CDX - 11/32" - 15/32" - 19/32" - 23/32"

MDO G2S - 1/2" - 3/4"

EDGE BANDING

www.veneertech.com

Hickory	Maple	White Birch
Red Oak	Walnut	Cherry
Melamine Edge Banding	PVC Edge Banding	

HARDWOOD VENEERS

www.formwood.com

Paperback	Polyback
Wood Back	P&S

SOFTWOOD LUMBER

Western Cedar - 1x6, 1x8, 1x12, 2x6, 2x8

Incense Cedar - 2x6, 2x8

Sugar Pine - 1x12, 2x12

Cypress - 1x6

Heat Treated Lumber (16ft Length) - 1x4, 1x8, 2x4, 4x4

(Unit Quantities Only on Heat Treated Lumber)

MOHAWK BRAND STAINS

www.mohawk-finishing.com

WILSON ART LAMINATES

www.wilsonart.com

MISCELLANEOUS

Sealer	Lacquer
Adhesives	Routing Bits
Screws	Saw Blades
Shims	Varnish
Wood Glue	

LET HOOD HELP YOU WITH YOUR SPECIALTY NEEDS

On-Time, On Grade, Competitively Priced

#Hoodwoodisgood

EST. 1899

HOOD DISTRIBUTION - NHLA LUMBER GRADES

This chart summarizes the main requirements for the standard grades. For complete information, consult the appropriate section of the NHLA Rule Book.

	FAS	FIF	SELECT	#1 COM	#2 & 2B	#3A COM	#3B COM	FAS LIMITS	
Minimum Size Board	6" x 8'	Same as FAS for species being graded	4" x 6'	3" x 4'	3" x 4'	3" x 4'	3" x 4'	PITH= SM in inches Wane= 1/2 Length Knot= 1/3 SM Warp= Entire board must be flat enough to S2S to S.S.T. Splits: not to exceed 2 x SM or 12" whichever is greater. Splits shall not diverge 1" in 12" First Lineal Foot Rule: Applies to both ends of Board, to contain not over 25% unsound wood.	Wane in FASIFACE: FAS transmission applies to better face. #1 Common Side: 1/3W or 1/2L Widest wane added together: Length can be on both edges.
Minimum Size Cutting	4" x 5' 3" x 7'	BETTER FACE TO GRADE FASPOOR FACE TO GRADE #1 COMMON		4" x 2' 3" x 3'	3" x 2'	3" x 2'	Not less than 1 1/2" wide containing 36 sq. inches		
Basic Yield	SM x 10 83-1/3%		SM x 8 60-2/3%	SM x 6 50%	SM x 4 33-1/3%	SM x 3 25%			
Formula to Determine Number of Cuts	SM — 4 (4 max.)		SM+1 — 3 (5 max.)	SM — 2 (7 max.)	Unlimited	Unlimited Sound Cuttings			
SM Needed to Take Extra Cutting	6-15' SM		3-10' SM	2-7' SM					
Extra Yield Needed for Extra Cutting	SM x 11 91-2/3%		SM x 9 75%	SM x 8 66-2/3%					
Special Yields	97% Rule -2 cuts full width any length; Pcs. 6" & wider with 6-12" SM SM x 11.64 for Yield		97% Rule On Better Face	2 + 3 SM to be 100% clear or SM x 11 in one cutting on Better Face. 97% Rule	1' SM- 100% 2' SM SMx 9	1' SM SMx 8 2A Com- Clear Face Cuttings 2B Com- Sound Cuttings	2A Com on Better Face and reverse side of cuttings sound; will also qualify for 3A Com		

#hoodwoodisgood

On-Time, On Grade, Competitively Priced

Est 1899