



## Material Safety Data Sheet

Copyright, 2007, NorthStar Chemicals, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing NorthStar Chemicals products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from NorthStar Chemicals, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Premier™ PB923 Canister  
**MANUFACTURER:** NorthStar Chemicals, Inc.  
**ADDRESS:** 19 Smiley Ingram Rd., Cartersville, GA 30120

EMERGENCY PHONE: CHEMTREC 1-800-424-9300

**Issue Date:** 01/05/2007  
**Supersedes Date:** Initial Issue

**Document Number:**

**Product Use:** Intended Use: Adhesive

### SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt.</u>
Dimethyl Ether	115-10-6	15-25%
Hexane	110-54-3	10-20%
Acetone	67-64-1	10-20%
Toluene	108-88-3	5-15%
Isobutane	75-28-5	5-10%
Propane	74-98-6	5-10%

### SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Immediate health, physical, and environmental hazards:** Closed containers exposed to heat from fire may build pressure and explode. Extremely flammable liquid and vapor. Contact with aluminum or zinc in a pressurized system may generate hydrogen gas which could create an explosion hazard.

Contains a chemical or chemicals which can cause cancer. May cause taraget organ effects.

## 3.2 POTENTIAL HEALTH EFFECTS

### Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

### Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Intentional concentration and inhalation may be harmful or fatal.

May be absorbed following inhalation and cause target organ effects.

### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

### Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/Symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness and unconsciousness.

Prolonged or repeated exposure may cause:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination

## SECTION 4: FIRST AID MEASURES

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed:

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## SECTION 5: FIRE FIGHTING MEASURE

## 5.1 FLAMMABLE PROPERTIES

<b>Flammability:</b>	Flammable per industry standard flame projection test
<b>Auto ignition temp</b>	Not Established
<b>Flash Point</b>	-156 degrees F (-104 degrees C)
<b>Flammable Limits-LEL</b>	1.8
<b>Flammable Limits-UEL</b>	18

## 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide)

## 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Accidental Release Measures:** Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Cover spill area with a fire-extinguishing foam. An aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected mater as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

## SECTION 7: HANDLING AND STORAGE

### 7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. keep away from heat, sparks, open flame, pilot lights and other sources of ignition. No smoking while handling this material. Avoid breathing of vapors, mists or spray. Avoid eye contact with vapors, mists, or spray. Keep out of reach of children. Vapors mayignite explosively. May cause flash fire. Prevent build-up of vapors - open all windows and doors. Maintain vapor concentrations below recommended exposure limits. Use only with cross-ventilation. Without adequate ventilation, vapors may settle in low-lying areas. Keep away from heat, sparks, and open flames. Do not smoke or ignite matches, lighters, etc. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure limits. If ventilation is not adequate, use respiratory protection equipment.

### 7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container tightly closed. Store away from oxidizing agents.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide appropriate local exhaust ventilation on open containers. Use in an enclosed process area is recommended. Do not use in a confined area or areas with little or no air movement. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use protection equipment.

### 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

#### 8.2.1 Eye/Face protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Safety Glasses with side shields. Indirect Vented Goggles.

#### 8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Polyvinyl Alcohol (PVA), Polyethylene/Ethylene Vinyl Alcohol.

#### 8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Conduct air monitoring to determine adequacy of ventilation and the need for respiratory protective equipment. If ventilation is inadequate select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface pressure demand self-contained breathing apparatus. Consult your personal protection supplier for further information.

#### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

### 8.3 EXPOSURE GUIDELINES

Ingredient	Authority	Type	Limit	Additional Information
Acetone	ACGIH	TWA	500 ppm	Table A-4
Acetone	ACGIH	STEL	750 ppm	Table A-4
Acetone	OSHA	TWA, Vacated	750 ppm	
Acetone	OSHA	TWA	1000 ppm	Table Z-1
Acetone	OSHA	STEL, Vacated	1000 ppm	
Dimethyl Ether	AIHA	TWA	1000 ppm	
Dimethyl Ether	CMRG	TWA	1000 ppm	
Hexane	ACGIH	TWA	50 ppm	Skin Notation*
Hexane	OSHA	TWA Vacated	50 ppm	Table Z-1A
Hexane	OSHA	TWA	500 ppm	Table Z-1A
Isobutane	ACGIH	TWA	1000 ppm	
Propane	ACGIH	TWA	1000 ppm	
Propane	OSHA	TWA	1000 ppm	Table Z-1
Toluene	ACGIH	TWA	20 ppm	Table A4
Toluene	CMRG	STEL	75 ppm	Skin Notation*
Toluene	OSHA	TWA Vacated	100 ppm	
Toluene	OSHA	STEL Vacated	150 ppm	
Toluene	OSHA	TWA	200 ppm	Table Z-2
Toluene	OSHA	CEIL	300 ppm	Table Z-2

VAC Vacated PEL: Vacated Permissible Exposure Limits (PEL) are enforced as the OSHA PEL in some states. Check with your local regulatory agency.

## SOURCES OF EXPOSURE LIMIT DATA:

<b>ACGIH:</b>	<b>American Conference of Governmental Industrial Hygienists</b>
<b>AIHA:</b>	<b>American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)</b>
<b>CMRG:</b>	<b>Chemical Manufacturer Recommended Guideline</b>
<b>EPA:</b>	<b>Environmental Protection Agency</b>
<b>IARC:</b>	<b>International Agency for the Research on Cancer</b>
<b>NIOSH:</b>	<b>National Institute for Occupational Safety and Health</b>
<b>NTP:</b>	<b>National Toxicology Program</b>
<b>OSHA:</b>	<b>Occupational Safety and Health Administration</b>

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Odor, Color:</b>	<b>Strong solvent odor, clear to light tan or red</b>
<b>Boiling point</b>	<b>-44 degrees F (-42 degrees C)</b>
<b>Vapor Density</b>	<b>Not Established</b>
<b>Vapor Pressure</b>	<b>Not Established</b>
<b>Specific Gravity</b>	<b>.70 to .74 gms/cc (5.8 to 6.2 lbs/gal)</b>
<b>Solubility in Water</b>	<b>Negligible</b>
<b>Volatile Organic Compounds</b>	<b>&lt;63% weight</b>

## SECTION 10: STABILITY AND REACTIVITY

**Stability:** Stable.

**Materials and Conditions to Avoid:** Sparks and/or flames

**Hazardous Polymerization:** Hazardous polymerization will not occur.

### **Hazardous Decomposition or By-Products**

<u>Substances</u>	<u>Condition</u>
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Bromide	During Combustion
Irritant Vapors or Gases	During Combustion

## SECTION 11: TOXICOLOGICAL INFORMATION

**Carcinogenicity:** No data available

## SECTION 12: ECOLOGICAL INFORMATION

Not determined.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14: TRANSPORT INFORMATION

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

## SECTION 15: REGULATORY INFORMATION

### US FEDERAL REGULATIONS

#### 311/312 Hazard Categories:

Fire Hazard - Yes    Pressure Hazard - Yes    Reactivity Hazard - No    Immediate Hazard - Yes    Delayed Hazard - Yes

#### Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
Hexane	110-54-3	10-20%
Toluene	108-88-3	5-15%

This material contains a chemical which required export notification under TSCA Section 12(b):

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No.</u>	<u>Regulation</u>	<u>Status</u>
Hexane	110-54-3	Toxic Substances Control Act (TSCA) 4 Text Rule Chemicals	Applicable
Acetone	67-64-1	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable

### STATE REGULATIONS CALIFORNIA PROPOSITION 65

The components in this product are in compliance with the chemical notification requirements of TSCA:

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Classification</u>
Toluene	108-88-3	*Developmental Toxin

\*WARNING: contains a chemical or chemicals which can cause birth defects or other reproductive harm.

## SECTION 16: OTHER INFORMATION

#### NFPA Hazard Classification

Health: 2

Flammability: 3

Reactivity: 0

Special Hazard: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

No revision information is available.

DISCLAIMER: This information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued.

NORTHSTAR CHEMICALS MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF

PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the NorthStar Chemicals product is fit for a particular purpose and suitable for users' method of use or application. Given the variety of factors that can affect the use and NorthStar Chemicals provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, NorthStar Chemicals makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from NorthStar Chemicals. application of a NorthStar Chemicals product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the NorthStar Chemicals product to determine whether it is fit for a particular purpose and suitable for users' method of use of application.

**MSDS are available at [www.northstarchemicals.com](http://www.northstarchemicals.com)**