



Material Safety Data Sheet

Copyright, 2007, NorthStar Chemicals, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing NorthStar Chemicals products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from NorthStar Chemicals, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PREMIER BOND PB925 Canister

MANUFACTURER: NorthStar Chemicals, Inc.

ADDRESS: 19 Smiley Ingram Rd., Cartersville, GA 30120

EMERGENCY PHONE: CHEMTREC 1-800-424-9300

Issue Date: 04-15-09

Supersedes Date: Initial Issue

Document Number: 1000-79

Product Use: Intended Use: Adhesive

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt.</u>
Methylene Chloride	75-09-2	40-50%
Dimethyl Ether	115-10-6	15-25%
Isobutane	75-28-5	5-10%
Propane	74-98-6	5-10%

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Immediate health, physical, and environmental hazards: Closed containers exposed to heat from fire may build pressure and explode. Extremely flammable liquid and vapor. Contact with aluminum or zinc in a pressurized system may generate hydrogen gas which could create an explosion hazard.

Contains a chemical or chemicals which can cause cancer. May cause target organ effects.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Intentional concentration and inhalation may be harmful or fatal.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/Symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness and unconsciousness.

Prolonged or repeated exposure may cause:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed:

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURE

5.1 FLAMMABLE PROPERTIES

Flammability: Flammable per industry standard flame projection test

Auto ignition temp Not Established

Flash Point -156 degrees F (-104 degrees C)

Flammable Limits-LEL 1.8

Flammable Limits-UEL 18

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide)

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only with non sparking tools. Ventilate the area with fresh air. Contain spill. Mix in sufficient absorbent until it appears dry. Collect waste and dispose of in accordance with local, state and federal laws and regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Avoid breathing of vapors, mists or spray. Avoid eye contact with vapors, mists, or spray. Keep out of reach of children. May cause flash fire. Use only with ventilation. Use general ventilation. If ventilation is not adequate, use respiratory protection equipment.

7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container tightly closed. Store away from oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide appropriate local exhaust ventilation on open containers. Do not use in a confined area or areas with little or no air movement. Use general ventilation and/or local exhaust ventilation. If ventilation is not adequate, use protection equipment.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Safety Glasses with side shields. Indirect Vented Goggles.

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Polyvinyl Alcohol (PVA), Polyethylene/Ethylene Vinyl Alcohol.

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

Ingredient	Authority	Type	Limit	Additional Information
Dimethyl Ether	AIHA	TWA	1000 ppm	
Dimethyl Ether	CMRG	TWA	1000 ppm	
Isobutane	ACGIH	TWA	1000 ppm	
Methylene Chloride	ACGIH	TWA	50 ppm	Table A3
Methylene Chloride	OSHA	TWA	25 ppm	
Methylene Chloride	OSHA	STEL	125 ppm	
Propane	ACGIH	TWA	1000 ppm	
Propane	OSHA	TWA	1000 ppm	Table Z-1

SOURCES OF EXPOSURE LIMIT DATA:

ACGIH:	American Conference of Governmental Industrial Hygienists
AIHA:	American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)
CMRG:	Chemical Manufacturer Recommended Guideline
EPA:	Environmental Protection Agency
IARC:	International Agency for the Research on Cancer
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Odor, Color:	Strong solvent odor, clear or red in color
Boiling point	-44 degrees F (-42 degrees C)
Vapor Density	Not Established
Vapor Pressure	Not Established
Specific Gravity	.86 to .90 gms/cc (7.1 to 7.5 lbs/gal)
Solubility in Water	Negligible
Volatile Organic Compounds	35% weight
VOC Less H2O & Exempt Solvents	<450 gms/liter

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: Sparks and/or flames

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substances</u>	<u>Condition</u>
Aldehydes	During Combustion
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Class Description</u>	<u>Regulation</u>
Methylene Chloride	75-09-2	Group 2B	International Agency for Research on Cancer
Methylene Chloride	75-09-2	Anticipated Human carcinogen	National Toxicology Program Carcinogens
Methylene Chloride	75-09-2	Cancer hazard	OSHA Carcinogens

SECTION 12: ECOLOGICAL INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

Liquefied Gas, Flammable, N.O.S. (Contains Dimethyl Ether, Methylene Chloride) 2.1, UN 3161

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No.</u>	<u>% by Wt.</u>
Methylene Chloride	75-09-2	40-50%

STATE REGULATIONS CALIFORNIA PROPOSITION 65

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No.</u>	<u>Classification.</u>
Methylene Chloride	75-09-2	**Carcinogen

**WARNING: contains a chemical which can cause cancer.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2

Flammability: 3

Reactivity: 0

Special Hazard: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

No revision information is available.

DISCLAIMER: This information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued.

NORTHSTAR CHEMICALS MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the NorthStar Chemicals product is fit for a particular purpose and suitable for users' method of use or application. Given the variety of factors that can affect the use and application of a NorthStar Chemicals product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the NorthStar Chemicals product to determine whether it is fit for a particular purpose and suitable for users' method of use of application.

NorthStar Chemicals provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, NorthStar Chemicals makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from NorthStar Chemicals.

MSDS are available at www.northstarchemicals.com