



Hood Distribution

210 Finley Ave, Bldg. 7
Birmingham, AL 35204
Phone: 1-205-905-5220
Toll Free: 1-833-247-2969
www.hooddistribution.com
"FSC" Certified

DOMESTIC PLYWOOD

www.columbiaforestproducts.com

Alder
Birch White
Cypress
Knotty Pine
Maple Natural
Walnut
Red Oak
White Oak
Rustic Grades

Birch Natural
Cherry
Hickory
Mahogany
Maple White
Afr. Mahogany
Ash
Shop Grade
Beaded Plywood

Poplar - Poplar/Aspen - FIR - MDF - CROSSBAND CORES
** 4X8-4X10 ** CARB 2 / NAF / TSCA TITLE VI
"Purebond" NAF

THINK LIGHT WEIGHT PANELS

www.thinklight.com

The World's Lightest Thick Panels

REMANUFACTURING HARDWOODS

S2S - S4S - Straight Line Rip, Gang Rip and mouldings, T&G

MELAMINE - ROSEBURG

www.rfpco.com

White Black Hardrock Drawer sides
*Other colors in stock

DOMESTIC LUMBER

Alder Basswood Walnut
Birch Cherry Cypress
Hickory Maple Hard Maple Soft
Red Oak White Oak Poplar
Ash

IMPORT LUMBER

Red Grandis Jatoba
African Mah
Mahogany
Sapele

SOFTWOOD LUMBER

Furniture Grade Pine SYP
Aromatic Cedar Western Red Cedar
Prime Treated KDAT Trim Boards

EDGE BANDING

www.formwood.com

Hickory Maple White Birch
White Oak Red Oak White/Black
Walnut Cherry Mahogany
Prefinished - Pre glued - Peel & Stick

IMPORT PLYWOOD

Birch White Meranti/Lauan NZ Pine
Liner Russian Birch Maple
Drawer sides Light weight

RADIATA PINE PLYWOOD

www.aruacoply.com

MARINE PLYWOOD

www.rfpco.com

AB Fir / Starboard / MDO
RigidCore / Aqua Ply

KNAPE & VOGT

www.kv.com

Sliding Systems - Barn Door Hardware - Standards & Brackets - Kitchen & Bath

VERSATEX TRIM, SHEETS, BOARDS

www.versatex.com

NICHIHA

www.nichiha.com

Fiber Cement Exterior Cladding & Siding

CHOICE BRAND ADHESIVES

www.choicebrandadhesives.com

FORMICA LAMINATES

www.formica.com

STARBOARD

ST Panels & Custom Doors www.kingplastic.com

Colorcore Plastaball Color Board

COMPOSITE PANELS

Kerfkore Ultra-light MDF
Particleboard EXTIRA MDF
Medex MDF MDF Domestic
ARRIES MDF Medite Fire Rated MDF
Beaded MDF

* All panel products CARB2/TSCA Title VI

BENDING PLYWOOD

Meranti - Barrel Column //KERFCORE//

HARDWOOD VENEERS

www.formwood.com

Paper Back - Poly Back - Wood Back - Peel & Stick
Reconstituted Hardwood Veneers
Architectural Laid Up Hardwood Plywood Panels

MISCELLANEOUS

Tite Bond Glue www.titebond.com

Deerwood fasteners
Reclaimed lumber
Decorative panels
Tile board

LET HOOD HELP YOU WITH YOUR SPECIALTY NEEDS

On-Time, On Grade, Competitively Priced

#Hoodwoodisgood

EST. 1899

HOOD DISTRIBUTION - NHLA LUMBER GRADES

This chart summarizes the main requirements for the standard grades. For complete information, consult the appropriate section of the NHLA Rule Book.

	FAS	FIR	SELECT	#1 COM	#2 & 2B	#3A COM	#3B COM	FAS LIMITS	
Minimum Size Board	6" x 8'	Same as FAS for species being graded	4" x 6'	3" x 4'	3" x 4'	3" x 4'	3" x 4'	<p>PTTH= SM in inches Wane= 1/2 Length Knot= 1/3 SM Warp= Entire board must be flat enough to S2S to S.S.T. Splits: not to exceed 2 x SM or 12" whichever is greater. Splits shall not diverge 1" in 12" First Lineal Foot Rule: Applies to both ends of Board, to contain not over 25% unsound wood.</p>	<p>Wane in FASIFACE: FAS transmission applies to better face. #1 Common Side: 1/3W or 1/2L Widest wane added together. Length can be on both edges.</p>
Minimum Size Cutting	4" x 5' 3" x 7'			4" x 2' 3" x 3'	3" x 2'	3" x 2'	Not less than 1 1/2" wide containing 36 sq. inches		
Basic Yield	SM x 10 83-1/3%			SM x 8 60-2/3%	SM x 6 50%	SM x 4 33-1/3%	SM x 3 25%		<p>Wane in Selects: Pes. 6" & Wider FAS imitation applies to Better face. #1 Common side: 1/3W or 1/2L Widest wane added together. Length can be on both side. Pes. 4" & 5" Wide 1/3W or 1/2L applies to both faces. Add widest wane together. Add total length of wane from both edges.</p>
Formula to Determine Number of Cuts	SM _____ 4 (4 max.)	BETTER FACE TO GRADE FASPOOR FACE TO GRADE #1 COMMON		SM+1 _____ 3 (5 max.)	SM _____ 2 (7 max.)	Unlimited	Unlimited Sound Cuttings		
SM Needed to Take Extra Cutting	6-15' SM			3-10' SM	2-7' SM				
Extra Yield Needed for Extra Cutting	SM x 11 91-2/3%			SM x 9 75%	SM x 8 66-2/3%				
Special Yields	97% Rule-2 cuts full width any length; Pes. 6" & wider with 6-12" SM SM x 11.64 for Yield	97% Rule On Better Face	2 + 3 SM to be 100% clear or SM x 11 in one cutting on Better Face. 97% Rule	1' SM- 100% 2' SM SMK 9	1' SM SMK 8 2A Com- Clear Face Cuttings 2B Com- Sound Cuttings	2A Com on Better Face and reverse side of cuttings sound; will also qualify for 3A Com			

#hoodwoodisgood

On-Time, On Grade, Competitively Priced